



VEGA
acryl-siloxane paint for interiors

Description	Water-based paint composed of: acrylic resins in emulsion, aggregates, pigments, additives, bactericides, water repellents		
	specific weight		1,62-1,64
	pH		8-9
	thinner		water
Characteristics	gloss level		mat
	washability		good
	vapor permeability		good
	volatile organic components		VOC < 30 gr/lt
	environmental classification		A
Safety	no requirement for specific labelling		
Storage	1 year in the original packaging if stored between +5°C and +40°C		
Supports	It is applied on plasters, prefabricated panels, plaster, wood, water-based paints and old, well-preserved and adherent plasters. These grounds must be absorbent, flat, clean, healthy and dry. Old or crumbling surfaces must be cleaned and consolidated. Do not apply on surfaces subject to rising damp.		
Laying Rules	Laying and drying must be carried out between + 5°C and + 35°C, away from bad weather or excessive sun. When laying, avoid applying fresh material to dry material and do not use products from different batches on the same wall.		
Laying	Apply in two coats with a brush, roller or gun.		
	dilution	first coat	25%
		second coat	5-10%
	Interval between two passes		10-12 hours
	Cleaning of tools		water
Yield	for 2 coats		7-8 m ² /lt

This edition cancels and replaces any previous edition. It is the task of Messrs. Customers ensure that this document has not been canceled by a subsequent edition. Edition 2023