



## SABBIE

*rough paint with an irregular sandy effect*

Description	Paint composed of synthetic binders in aqueous emulsion, fine sands, quartz, dyes, additives, bactericides. specific weight pH thinner	1,45-1,49 8-9 water
Caratteristiche	water absorption environmental classification Sabbie contains granular aggregates which give the paint a rough appearance	very low A
Safety	no requirement for specific labelling	
Storage	1 year in the original packaging if stored between +5°C and +40°C	
Supports	Sabbie can be applied indoors or outdoors on flat, clean, healthy and dry surfaces. The prefabricated structures must not bear traces of release agents, the old or crumbling surfaces must be cleaned and consolidated. Plaster and wood must be treated with a suitable fixative. Do not apply on surfaces subject to rising damp	
Laying Rules	Laying and drying must be carried out between +5°C and +35°C, protected from bad weather or excessive sun. Do not apply materials from different batches on the same wall	
Laying	Apply a coat of fine-grained Fixaquarz as a primer. After drying, mix Sabbie well, without diluting it, and distribute it with short strokes made with a flat brush. The grains present in the paint tend to fall to the bottom during application. Shake the paint from time to time. Wash tools with water after use.	
Yield		5-6 m <sup>2</sup> /lt

*La presente edizione annulla e sostituisce ogni edizione anteriore. E' compito dei sigg. Clienti accertarsi che il presente documento non sia stato annullato da una edizione successiva. edizione 2023*